

452 C

## Small-budget top labelling machine

> Availability: At very short notice

> **Applicator:** The outstanding HERMA 400

> **Flexible:** Available in standard lengths\* of:

approx. 1000/1500/2000 mm, or 40/60/80"

and four standard widths:

50/100/150/250 mm, or 2/4/6/10"

\*individual lengths on request

Compact, reliable, state-of-the-art technology for top labelling of a wide range of products and food packaging, etc. The machine can be supplied either with a fixed dispensing beak and a sprung-loaded application roller or with a pivot beak. The pivot beak allows for the precise linear labelling of objects with large dimensional tolerances, irregularities or recesses (such as margarine packs, etc.).







Standard dispensing system: rigid beak with sprung-loaded application roller.

## Technical data of the 452 C

Products Length Any

Width 260 mm (10.2") with standard belt

Max. height 280 mm (11")

Labels Max. reel Ø 300 mm (12") (standard)

Width 120 mm (4.7") (max. standard)

Labelling speed Conveyor belt speed [m/min.]  $\times 1000 = \frac{\text{Products}}{\text{Conveyor}}$ 

Product length [mm] + gap [mm] min.

Power supply 230V / 50 Hz

115 V / 60 Hz

Power consumption Approx. 650 VA

We are constantly endeavouring to improve our products. All technical data is therefore subject to change without prior notice.

HERMA UK Ltd Labelling Systems Division The Hollands Centre Hollands Road Haverhill Suffolk CB9 8PR 01440 763366

www.herma.co.uk